

10.1" Panel Computer



SUMMARY

ID	30047	CPU OPTION:	NORTH INVENT PART NO:
COMPANY NAME	North Invent Norway	Intel Atom x6413E @ 1.5 GHz (3.0 GHz)	WE101 000 581
VAT	987884002VAT		
ADDRESS	Sørhauggata 128 5527 Haugesund NORWAY		

NB! To order optional PSU versions and / or I/Os listed on the next page, please ask your North Invent representative for the correct P/N.

REVISION HISTORY

APPROVED	CHECKED	DRAWN	STATUS	DESCRIPTION
2023.09.01 OKJ	2023.09.01 OKJ	2023.09.01 OKJ	Issued for Customer Review	First Revision, illustrations to be updated

10.1" Panel Computer

The North Invent 10.1" Panel Computer is a state-of-the-art computer concept, built with industrial extended temperature components.

Designed for 10 years of manufacturing, the North Invent 10.1" Panel Computer is boasting powerful 11th Generation Intel® Atom™ Processors.

It has 10 point PCAP multitouch integrated into a slim design.

As for all North Invent products the will unit remains fanless with low power consumption.



TECHNICAL SPECIFICATION 10.1" Panel Computer

MATCHING STANDARDS (Pending)

IEC 60945, IACS E10, EMC Directive-2014/30/EU, RoHS, REACH
Compliant to a selection of MIL standards

DISPLAY SIZE	10.1" - Active area 216.96 (W) X 135.60 (H) mm
OVERALL DIMENSIONS	242 (W) x 164 (H) x 58 (42) (D) mm
NET / GROSS WEIGHT	1.7 / 2.5 kg
RESOLUTION	Max 1280 x 800 pixels
RESPONSE TIME	13 ms (typ)
CONTRAST RATIO	800:1 (typ)
CPU	Intel® Atom x6413E @ 1.5 GHz (3.0 GHz)
LIGHT INTENSITY	700 cd/m2 (typ)
GRAPHICS	Intel® UHD Graphics (Gen11)
VIEWING ANGLE	±88°
SSD	32GB eMMC 5.1 onboard flash
SUPPLY VOLTAGE	18-36 VDC
POWER CONSUMPTION	Approx. 35W
RAM	4GB 3200MT7s LPDDRx onboard memory
ENCLOSURE PROTECTION	IP 67 from front given correct mounting and sealing.
GLASS TYPE	3.0 mm Tempered, Anti Reflective
INPUT/ OUTPUT	2 x 10/100/1000 Ethernet RJ45 with TPM 2.0, 1 x DisplayPort (DP++) output, 1x USB 3.1 Gen2 Type C, 2 x USB 3.1 Gen 2 Type A, 1 x RS232 (9-pin DSUB), 1 x RS422 (9-pin DSUB).
OPERATING / STORAGE TEMPERATURE	-15/+70° C, -15/+70° C (+5/+158° F, +5/+158° F)
BACKLIGHT LIFE	Typ 50.000 Hours
DIMMING RANGE	0-100%
OS SUPPORTED	Linux and Windows
TOUCH	10 Point PCAP Multitouch